

## HEAVY DUTY GAS FRYER 2 X 12L WITH FAUCET



<b>Power</b>	20.0 kW
<b>Connection</b>	1/2" G25 Natural Gas / G30 LPG
<b>Net Weight</b>	40 kg
<b>Machine Dimensions</b>	B800 x D700 x H280 mm
<b>HS Customs Code</b>	8419818090
<b>EAN Code</b>	8719632123798
<b>Article Number</b>	09395003



### GENERAL SPECIFICATIONS

- 1.5 mm thick AISI 304 stainless steel top
- Flush top setting with secure fixing screws
- Installation gap behind the equipment
- Easy access from front panel to all major components
- Stainless steel with satin Scotch-Brite finish
- Adjustable feet

### INSTALLATION OPTIONS

- standalone (fixed on a base w/ or w/o door)
- cantilever
- on concrete plinth

### GAS FLOW RATE

<b>68240 Btu/hr</b>	<b>17200 kcal</b>	
G20 Natural gas	20mbar	2.11 m <sup>3</sup> /h
G30/G31 LPG	28-30/37 mbar	1.57 kg/h
G30 LPG	50 mbar	1.57 kg/h

### GAS FRYER

- Well capacity 8 – 12L (W300 x D325 x H240 mm)
- Oil expansion recess incorporated in the top
- Continuous seal of the well on the top by robotic welding
- Interior of one piece deep drawn well with rounded corners for ease of cleaning
- Thermostatic regulation of oil temperature up to a maximum of 190°C
- Supplied with full size baskets per each well
- Safety thermostat with manual reset standart
- Burners tube located inside the well avoid food particles burning or spoiling the oil
- Jet burners made of mild steel 2 pieces for each well
- Easy draining with through a front tap
- Piezo spark ignition for added safety
- Thermostatic gas valve with flame failure device controlled each well with pilot burner

### ACCESSORIES

- Full sizes baskets for 12L wells – 1 Pcs
- Lid with ergonomic handle for 12L wells – 1 Pcs
- Baskets holder and base grid for 12L wells – 1 Pcs

